VL500 Adding APN



Before beginning this process, make sure WIFI is disabled.

STEP 1

Insert SIM card in SIM Slot 1. Please make sure the gold contact is facing down. Please note that there is a diagram displaying how to correctly insert the SIM card into the terminal.



STEP 2

Open the ValorPay app. Tap the **Main Menu icon ()** on the bottom of the screen.



Scroll down and tap Comm Config. Then Press Comm Config again.



STEP 4

Go to SIM Cards and make sure it is toggled to the Off position.





Tap the Back button, tap More, then tap Cellular Networks.



	Wireless & networks	2 R B 14045	
	Airplane mode	1.00	
	Wi-Fi calling		
I	Tethering & portable hotspot		
I	WHY		
	Cellular networks		
	Mobile plan		
	hietwork settings reset		
	0	A	





Hit the + on the top right of the screen and enter the Name & APN (you have to enter the APN in both fields.)

+ APNo			Edit access point [Edit access point
Data/05 Talkys Induits famos			Name Total and		APN
TIM WER But 101.0	0		APN Inst ser		Data00 Telnys
WAP TIM anap line 2	0		Pritray Not not		CANCEL OR
ITOM writes and a		\rightarrow	Port	\rightarrow	Talmod Tetnyx Telly &
			Usemane		$q^{\dagger} w^{*} e^{*} r^{*} t^{*} y^{*} u^{\dagger} i^{*} o^{*} p^{*}$
			Password		asd fghjki
			Not not		🝨 z x c v b n m 🖾
	4		Server The set		

STEP 8

Tap the Vertical Ellipsis (:) and tap Save.





Once back to the screen displaying the list of APNs, tap the APN you just added so that the circle has a smaller green circle inside. After about 30 seconds, the terminal will connect to GPRS

← APNs	⊕ I
Data00.Telnyx Data00 Telnys	۲
TIM WEB Box Sm It	0
WAP TIM wap fim.it	0
ITIM unico.tim.it	
0	0

