

SPECIFICATIONS

VL500 Android POS

Processor		High Speed Quad-Core 32-bit Processor plus Secure MCU	
Operating System		Android 9.0	
Memory	Flash/RAM	8GB/1GB (Up to 16GB/2GB)	
	Micro-SD Socket	Yes	
Display		5.5" 1280 x720 Color TFT Capacitive Touch Display	
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple Track, Bi-Directional	
	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
		SAM Card	2
		SIM Card	2
	Contactless	ISO 14443 Type A, B ISO 18092 NFC Mifare and Sony FeliCa Working Frequency 13.56MHz	
Communications Interface Options	Wireless	4G LTE/3G/GPRS WLAN Bluetooth	
	GPS	Yes	
Indicators	Audio	Speaker and 4 Pole Audio Jack Microphone	
Keypad		Virtual Keypad (Support PIN on Touch)	
Printer		57mm x 40mm (Paper Roll Size), 100mm/sec (Print Speed)	
Camera		5M Pixel AF with Flash Light Rear Camera	
Software		SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library	
Crypto		TRNG DES T'DES AES RSA MK/SK DUKPT	
Power Supply	DC	5V/2A	
	Battery	6000mAh/3.7V Li-ion Rechargeable Battery	
Dimensions (L x W x H)		200 x 78 x 56 (mm)	
Weight		495 g	
Environment	Operating Temperature	-10°C to 50°C	
	Storage Temperature	-20°C to 70°C	
	Operating Humidity	5% to 90% non-condensing	
	Storage Humidity	5% to 90% non-condensing	
Certification		PCI PTS 6.x EMV L1/L2 payWave PayPass ExpressPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2	
Additional Features		2M Pixel FF Front Camera Rear Barcode Reader	
Optional Accessories		Charging Cradle Communication Cradle	