

Processor		32-bit secure microprocessor running a powerful Linux-based operating system
Memory	Flash/DDRDRAM	128 MB/64 MB (up to 256 MB/128 MB)
	Micro-SD Socket	Yes
Display		3.5" Color TFT LCD 320 x 480 Pixels
Touchscreen		Yes
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple track, bi-directional
	Contact Card (User Card)	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
	Contactless (Optional)	ISO 14443 Type A, B ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz
Communications Interface Options	Wireless	Wi-Fi
	Wired	Ethernet
Indicators	LED - Contactless	No
	Audio Buzzer	Yes
Keypad	Standard Keys	15
	Function Keys	No
Printer		57 mm x 50 mm, 100 mm/sec
Software		SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library
Crypto		TRNG DES T'DES AES RSA MK/SK DUKPT T'DES DUKPT
Power Supply	Power Adapter	DC 9V/4A
Dimensions (mm)		190(L) x 78(W) x 78(H)
Weight		350 g
Environment	Operating Temperature	0°C to 50°C
	Storage Temperature	-20°C to 70°C
	Relative Humidity	5% to 90% non-condensing
Certifications		PCI PTS 4.x EMV L1/L2 payWave PayPass ExperssPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2



valorpaytech.com



Copyright © 2023, Valor PayTech, LLC. All rights reserved.

Reproduction, posting or distribution of this document or its contents is prohibited without the express written consent of Valor PayTech.



Scan to Contact
Sales Team.



1.800.615.8755

sales@valorpaytech.com