

Processor		32-bit secure microprocessor running a powerful Linux-based operating system
Memory	Flash/DDRDRAM	128 MB/64 MB (up to 256 MB/128 MB)
	Micro-SD Socket	Yes
Display		3.5" 320 x 480 TFT LCD
Touchscreen		Yes
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple track, bi-directional
	Contact Card (User Card)	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
	Contactless (Optional)	ISO 14443 Type A, B   ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz
	Dual SIM	Yes
Communications Interface Options	Handset	2G/3G/4G   Wi-Fi   USB
	Base	USB
Indicators	LED - 4	No
	Audio Buzzer	Yes
Keypad	Standard Keys	15
	Function Keys	No
Printer		57 mm x 40 mm, 100 mm/sec
Software		SDK   KMS   TMS   GDB   CTOS library   ISO 8583 library   Crypto library
Crypto		TRNG   DES   T'DES   AES   RSA   MK/SK   DUKPT   T'DES DUKPT
Power Supply	Power Adapter / USB	9V/4A   5V/1A
	Battery	Li-Polymer 3.7V ~ 4.2V 2100mAH
Dimensions (mm)	Terminal	160(L) x 78(W) x 67(H)
	Base	137.6(L) x 81(W) x 48.8(H)
Weight		335 g
Environment	Operating Temperature	0°C to 50°C
	Storage Temperature	-20°C to 70°C
	Operating Humidity	5% to 90% non-condensing
Certifications		PCI PTS 4.x   EMV L1/L2   payWave   PayPass   ExperssPay   D-PAS   Interac Flash   J-Speedy   FeliCa   UnionPay UICS   TQM   PBOC L1/L2



valorpaytech.com



Copyright © 2023, Valor PayTech, LLC. All rights reserved.

Reproduction, posting or distribution of this document or its contents is prohibited without the express written consent of Valor PayTech.



Scan to Contact  
Sales Team.



1.800.615.8755

sales@valorpaytech.com