

| | | |
|----------------------------------|--------------------------|---|
| Processor | | 32-bit secure microprocessor running a powerful Linux-based operating system |
| Memory | Flash/RAM | 256 MB / 128MB |
| Display | | 3.5" Color TFT LCD 320 x 480 Pixels |
| Touchscreen | | Yes |
| Card Reader | Magnetic Stripe | ISO 7810, 7811, 7813 Triple track, bi-directional |
| | Contact Card (User Card) | ISO 7816 ID-1 1.8V/3V/5V T=0, T=1 |
| | Contactless (Optional) | ISO 14443 Type A, B ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz |
| Communications Interface Options | Wired | Ethernet |
| Audio | | Speaker |
| Keypad | Standard Keys | 15 |
| Software | | SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library |
| Dimensions (mm) | | 150(L) x 78.5(W) x 39(H) |
| Weight | | 225g |
| Environment | Operating Temperature | 0°C to 50°C |
| | Storage Temperature | -20°C to 70°C |
| | Relative Humidity | 5% to 90% non-condensing |
| Certifications | | PCI PTS 4.x EMV L1/L2 payWave PayPass ExperssPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM |




valorpaytech.com



Copyright © 2023, Valor PayTech, LLC. All rights reserved.

Reproduction, posting or distribution of this document or its contents is prohibited without the express written consent of Valor PayTech.



Scan to Contact
Sales Team.



1.800.615.8755

sales@valorpaytech.com