



VP100 The Innovative Countertop Solution

Experience the future of payments with VP100, the innovative countertop solution featuring a user-friendly display and cutting-edge features.

User-friendly and Intuitive Experience

Enjoy a user-friendly experience with a spacious touchscreen display on our intuitive interface with digital signature capture feature with print, SMS, or email receipt options. The VP100 offers effortless bill splitting functionality tailored to group payments to enhance convenience.

Secure and Convenient Contactless Payments

Embrace the future of payments through cutting-edge EMV card technology, offering swipe, tap, and dip card payment options along with EBT-enabled devices, catering to a wide range of customers' needs.

Advanced Technological Expertise

The VP100 offers flexible processing with dual merchant IDs (MIDs), uninterrupted service with the auto-connection failback procedure, and enhanced Ethernet and Wi-Fi options, ensuring secure and reliable services.

SMS & Email Marketing Opportunities

Increase customer loyalty with our Engage My CustomerTM via personalized SMS and email campaigns, enhancing brand awareness. Utilize our integrated feedback rating system for insights to refine services and elevate customer satisfaction.

Features



Large Scale 3.5" Touchscreen Display



FBT Fnabled



Dual MID Supported Technology



SMS & Email Marketing With Engage My Customer™



Ethernet and Wi-Fi Connectivity



Full Transaction Information Display



Auto-Connection Failback Procedure



Bill Splitting



Digital Signature Capture with SMS & Receipt options



Built-in Customer Feedback Rating System

Specifications



	32-bit secure microprocessor running a powerful Linux-based operating system
Memory Flash/DDRRAM Micro-SD Socket	128 MB/64 MB (up to 256 MB/128 MB)
	Yes
	3.5" Color TFT LCD 320 x 480 Pixels
	Yes
Magnetic Stripe	ISO 7810, 7811, 7813 Triple track, bi-directional
Contact Card (User Card)	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
Contactless (Optional)	ISO 14443 Type A, B ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz
Wireless	Wi-Fi
Wired	Ethernet
LED - Contactless	No
Audio Buzzer	Yes
Standard Keys Keypad Function Keys	15
	No
	57 mm x 50 mm, 100 mm/sec
	SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library
	TRNG DES T'DES AES RSA MK/SK DUKPT T'DES DUKPT
Power Adapter	DC 9V/4A
	190(L) x 78(W) x 78(H)
	350 g
Operating Temperature Environment Storage Temperature Relative Humidity	0°C to 50°C
	-20°C to 70°C
	5% to 90% non-condensing
	PCI PTS 4.x EMV L1/L2 payWave PayPass ExperssPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2
	Micro-SD Socket Magnetic Stripe Contact Card (User Card) Contactless (Optional) Wireless Wired LED - Contactless Audio Buzzer Standard Keys Function Keys Power Adapter Operating Temperature Storage Temperature





🖂 sales@valorpaytech.com

valorpaytech.com

f X ☑ □ in

Scan to Contact Sales Team

