

Specifications

Processor		Cortex Quad-core A53, 2.0GHz
Security Processor		ARMv7-M security core
Operating System		Android
Memory	Flash/RAM	2GB
	Micro-SD Socket	(Up to 256GB)
Display		5.99-inch TFT full color LCD display, resolution of 1440 x 720, with adjustable backlight, capacitive multi-touch screen, support electronic signature
Magnetic Card Reader		Triple track, bi-directional, conforming to ISO 7810/7811/7813
Smart Card Reader		EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1
Contactless Card Reader		EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica
Positioning		GPS, GLONASS, BEIDOU
Wireless Communication		4G / 3G Wi-Fi (802.11 a/b/g/n/ac) 2.4G&5G Bluetooth 2.1/5.0
Audio		1 x speaker, 1 x microphone, support audio recording and media play
Keypad		Secure virtual keypad for PIN entry, 1 x power button, 1 x VOL+, 1 x VOL-
Printer		High-speed thermal printer, 80 mm/s Paper roll diameter: 40mm Paper width: 58mm
Camera		0.3 MP front camera, support 1D/2D code payment 5 MP autofocus rear camera with flashlight, support 1D/2D code payment
Peripheral Ports		1 x Type C port
Card Slots		2 x SIM, 2 x SAM, 1 x SD
Battery		Li-ion battery, 7.2V/2600mAh/18.7Wh (Equal to 3.6V/5200mAh)
Power supply		Input: 100-240V AC 50/60Hz Output: 5.0V DC, 2.0A
Dimensions (mm)		201(L) x 79.8(W) x 62(H)
Expansion HUB		RS232 (RJ12/RJ11), 2 x USB-A, Type-C, Ethernet (RJ45)
Weight		464g including battery
Environment	Operating Temperature	-10°C~50°C (14°F~122°F)
	Storage Temperature	-20°C~60°C (-4°F~104°F)
	Relative Humidity	5%~93% (Non-condensing)
Docking Station		N/A
Certifications		PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, JCB, TQM, CE, RoHS, MCCC, CB, Interac, ATEX



☎ 1.800.615.8755
✉ sales@valorpaytech.com
🌐 valorpaytech.com



Scan to Contact
Sales Team

