

## Specifications

OS	Linux	
CPU	Dual-core Cortex A7, 1GHz + Secure Processor	
Memory	256MB RAM, 256MB FLASH , Micro SD (up to32GB)	
Display	3.5-inch TFT full color LCD display, resolution of 320 x 480 Capacitive touchscreen, support electronic signature	
Card Reader	Magnetic Card	Triple track, bi-directional, conforming to ISO 7810/7811/7813
	Smart Card	EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1
	Contactless	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare, Felica, HCE
Audio	Speaker 1.5W	
Keypad	10 x numeric keys, 5 x function keys, back light	
Communication	USB Device, Ethernet 10/100M	
Power Supply	Input: AC 100~240V Output: DC 5V/2A	
Accessories	Kensington lock, Privacy Shield, Rotatable mount	
Dimensions (mm)	163mm (L) x 74mm (W) x 31mm (H) Without Privacy Shield 163mm (L) x 74mm (W) x 46mm (H) With Privacy Shield	
Weight	252g	
Environment	Operating temperature	10°~50° (14°~122°)
	Storage temperature	20°~70° (-4°~158°)
	Relative humidity	5%~95% (non-condensing)
Certifications	PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave American Expresspay Discover D-PAS, AMEX, QuickPass, TQM, RoHS, CE, ANATEL, ABECS, FCC, JCB, UPTS 3.0	



1.800.615.8755  
sales@valorpaytech.com  
valorpaytech.com



Scan to Contact Sales Team

