

Specifications

CPU		Dual-core Cortex A7, 1GHz
Memory	Flash/RAM	256MB/256MB
Display		3.5-inch color TFT LCD featuring a capacitive touchscreen, offering a resolution of 320 x 480 pixels and supports electronic signature capture
Card Reader	Magnetic Card	Triple track, bi-directional, conforming to ISO 7810/7811/7813
	Smart Card	EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1
	Contactless	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare, Felica, HCE
Audio		Speaker 1.5W
Keypad		10 x numeric keys, 5 x function keys, back light
Connectivity		RS232 serial, USB device
Power Supply		Input: AC 100~240V Output: DC 5V/2A
Accessories		Kensington lock, Privacy Shield, Rotatable mount
Dimensions (mm)		163mm (L) x 74mm (W) x 31mm (H) Without Privacy Shield 163mm (L) x 74mm (W) x 46mm (H) With Privacy Shield
Weight		252g
Environment	Operating temperature	10°~50° (14°~122°)
	Storage temperature	20°~70° (-4°~158°)
	Relative humidity	5%~95% (non-condensing)
Certifications		PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave American Expresspay Discover D-PAS, AMEX, QuickPass, TQM, RoHS, CE, ANATEL, ABECS, FCC, JCB, UPTS 3.0



1.800.615.8755

sales@valorpaytech.com

valorpaytech.com



Scan to Contact
Sales Team

